



AIC Inc.
No. 9, Alley 19, Lane20
Da Hsing Rd. Luchu Township, Taoyuan, Taiwan
TEL: +886-03-3138386
FAX: +886-03-3138377

XJ3000-4243S Hot-Swap SSG JBOD Functionality Test Report

Formal Release

Initiated by	Reviewed by	Approved by
<div>DQA 2013.04.03 Jack Huang</div>	<div>DQA 2013.04.10 Tony Wang</div>	<div>QD & SCM 2013.04.10 David Yu</div>
Originate Date	Revision	Release Status
2013/4/3	A3	Formal Release

Copyright©2013 AIC Inc. This document contains information proprietary to AIC Company .
Use or disclosure without written permission of an officer of AIC expressly forbidden.

Revision History

Revisions

REV.	DESCRIPTION	DATE	Engineer
A0	XJ3000-4243S hot-swap JBOD Functionality Test	2012/10/15	Jeffery Lu
A1	Cascading JBOD Test	2012/10/26	Jeffery Lu
A2	ECN (B/P, F/W upgrade)Firmware :1.11.5.7 MFG:1.5.0.3 Validation Test	2012/12/18	Jeffery Lu
A3	ECN: MFG Upgrade, F/W: 1.11.5.7 MFG: 1.5.0.5, Functional Test: Fan stop spinning under low temperature / Mis-configure 2U24swap and 2U24swap2	2013/4/3	Jack Huang

If product change or information change/update, the report will be revised and released next edition.

Date of Test:

Test Started	Test Completed
2013/4/1	2013/4/3

Copyright©2013 AIC Inc. This document contains information proprietary to AIC Company .
Use or disclosure without written permission of an officer of AIC expressly forbidden.

Table of Contents

1 Introduction.....	4
1.1 Scope.....	4
1.2 Purpose.....	4
1.3 Reference Information.....	4
2 Plan of Action Reference.....	5
2.1 Plan of Action Procedure.....	5
2.2 Test Reporting.....	5
3 Product Specification.....	6
3.1 Product Features.....	6
3.2 Product Specifications.....	6
3.3 DUT 45° Photo.....	7
4 DUT Images.....	8
5 Target Device Configuration and Environment.....	9
5.1 Table of Test Configuration.....	9
5.2 DUT Main Hardware Configuration.....	9
6 Function Test.....	10
7 RAID Card Test.....	14
8 Summary.....	15

Copyright©2013 AIC Inc. This document contains information proprietary to AIC Company .
Use or disclosure without written permission of an officer of AIC expressly forbidden.

1 Introduction

1.1 Scope

This document is for demonstrating product conformance in the Various Development Phases of a project.

1.2 Purpose

Provide a formal and consistent process for measuring and validation the reliability of a given design. Identify any design discrepancies or electrical, mechanical, firmware and system issues.

1.3 Reference Information

The following documents form a part of this test plan to the extent specified herein.

- DVT Requirements Document
- Current Hardware Platform Evaluation Test Plan

Owner	Document List Review
PM	Application form for DVT functionality validation
PM	Product specification
EE1	Product EVT test report
QT	Board level compatibility EVT test report
EE1	PCB Schematic / Layout

2 Plan of Action Reference

2.1 Plan of Action Procedure

- Refer to this document or other identified specification to start product testing.
- Identify all necessary requirements and equipment for the test.
 - All equipment must be calibrated on an annual basis. Documentation of the calibration must be available.
 - Proper maintenance of equipment is required.
- Complete testing according to instructions or procedures contained in this document.
- Identify whether or not product or product component passes or fails.
- Report all test results to DQA designated personnel and database.
 - Within the Problem Tracking System, the function test shall be referenced in the short description of the issue.
- The EE design teams have the responsibility to resolve all issues and concerns by PVT date.
- Identified issues and concerns will be worked in order of priority and resolved according to the mechanical checklist and any associated documented specifications.
- The QAE team may identify resolution for an issue regarding a product in the design process, if it is deemed necessary for the QAE team to be involved.

2.2 Test Reporting

Throughout the process of development, all progress in testing must be tracked and communicated to the DQA weekly.

Each test shall be tracked as follows:

Definition	Description
Pass	All units were able to complete testing within the specified Pass Criteria.
Fail	UUT were not able to complete testing within the specified Fail Criteria
Bug	Unable to predict potential problems
Pending	Test initially failed but is able to pass after fixes were implemented

All Pass/Fail data results must be repeatable.

3 Product Specification

3.1 Product Features

Title	XJ3000-4243S Hot-Swap JBOD
	XJ3000-4243S Entry-Level SAS/SATA 6G JBOD Series
Features	24*6G SAS/SATA hard disk bays with lock
	4*hot-swap fans
	Hot-swap 600W 12V high-efficiency redundant power supply module
	3*24Gb/s Mini SAS ports with single expander 6*24Gb/s Mini SAS ports with dual expanders
	Serial port for console monitoring

3.2 Product Specifications

GENERAL

Number of Expander	Single/Dual
Expander Chip	LSISAS2x36
Host Interface	Mini SAS 4x connector
Expansion Interface	Mini SAS 4x connector
Transfer Speed	2,400MB/s per connector

DRIVES SUPPORTED

Drive Interface	3.0/6.0 Gb dual ported SAS 1.5/3.0/6.0 Gb single ported SATA
Drive RPM	Up to 15,000
Form Factor	3.5", 1"height

ADMINISTRATION / MANAGEMENT

Admin/Firmware Upgrade	In-band Serial port via Hyperterminal
LED Indicators, Alarm	Yes

HOT-SWAP & REDUNDANCY

Disk Drive	Hot-swap 24-bay
Cooling	4 x hot-swap fans
Power Supplies	600W 1+1 hot-swap redundant 80+ (Silver)
Power Entry	Dual AC Inlet

ELECTRICAL & ENVIRONMENTAL

Universal A/C Input	100~240V AC full range
Operating Environment	Temperature 0°C to 35°C, Relative humidity 20% to 80%
Non-operating Environment	Temperature -20°C to 60°C, Relative humidity 10% to 90%

PHYSICAL SPECIFICATION

Dimensions (W x D x H)	mm	430 x 533.2 x 174
	inches	17x21x7
Packaging Dimension (W x D x H)	mm	590 x 785 x 335
Mounting Option	Adjust plate or 20" tool-less rail (optional)	

3.3 DUT 45° Photo



4 DUT Images



Front Angle



Top Open Angle



Rear Angle

5 Target Device Configuration and Environment

5.1 Table of Test Configuration

Host Configuration					
Item		Vender / Model		Detail	
Morththerboard		AIC Gemini ver.D		Motherboard of the host	
Operation System		Microsoft Windows		Server 2008 R2 64bit	
CPU		Intel		Xeon X5677 3.47GHz *1	
Memory		DSL		DDR3 1066 U-DIMM/ 1GB *2	
Hard Disk Drive		Seagate / ST9160511NS		SATA HDD / 160GB *1	
RAID Card Configuration					
Card	Vender / Model	Firmware ver.	BIOS ver.	Driver ver.	GUI Software ver.
RAID Card	Intel RS2PI008	2.130.363-1846	3.25.00_4.12.05.00	5.2.116.64	12.05.03.00
RAID Card	Adaptec 6405	5.2-0(19109)	5.2-0(19109)	7.1.0.30034	7.31.00(18856)
XJ3000-4243S JBOD HDD Configuration					
Vender / Model		Interface		Detail	
Fujitsu / MBA3073RC		SAS 3G		73.5GB, F/W:0103	
Seagate / ST3600057SS		SAS 6G		600GB, F/W:0008	
Seagate / ST3600002SS		SAS 6G		600GB, F/W:0008	
Seagate / ST31000424SS		SAS 6G		1TB, F/W:0006	
Seagate / ST1000NM0001		SAS 6G		1TB, F/W:0001	

5.2 DUT Main Hardware Configuration

Item	Product Number	Quantity	Detail
Backplane	B40-4ATKXXXX00A110	1	4U24S Hot Swap 6G JBOD SN: 505-12102600310145
Power Housing	Zippy R2G-5600V4V	1	AC INPUT:100-240V 47-63Hz 9-4A DC OUTPUT:600W(MAX)
Power Module	Zippy GIN-3600V	2	AC INPUT:100-240V 47-63Hz 9-4A
Expander IO board	B46-LKSAXXE-00A210	2	1. SN: 506-12091000110001 (sas addr: 50015B216806BC3F) 2. SN: 506-12102600110299 (sas addr: 50015B2168033E3F)
Fan Module	SUNON PSD1206PMB1-A	2	DC 12V/ 9.8W

6 Functional Test

Test Engineer	Jack Huang		
Model Name	XJ3000-4243 Swap		
Firmware	1.11.5.7		
MFG	1.5.0.5		
Expander Board	B46-LKSAXXE-00A210 1. SN: 506-12091000110001 2. SN: 506-12102600110299		
Backplane	B40-4ATKXXXX00A110 SN: 505-12102600310145		
RAID Card	Intel RAID RS2PI008	Driver	5.2.116.64
Power Housing	Zippy R2G-5600V4V AC INPUT: 100-240V 47-63Hz 9-4A DC OUTPUT: 600W(MAX)		
Power Module	Zippy GIN-3600V AC INPUT: 100-240V 47-63Hz 9-4A		

Item Test	Power Module		
Test Procedure			Result
Hot swap the power module and power cord, confirm the right side of functions are work normally.	Hot-swap PSU under power on state, check fail led, beeper, and console status.		Pass
	Power cord interrupt, check fail led, beeper, and console status.		Pass
	PSU status under GUI		Pass
	PSU status under console		Pass

Item Test	System FAN		
Test Procedure			Result
Hot swap or start/ stop the FAN module, and confirm the right side of functions are work normally.	How-swap fan under power on state, check fail led, beeper, GUI, and console status.		Pass
	Fan status under GUI		Pass
	Fan status under console		Pass
	Smart Fan, if temperature upgrade, the rotational speed of fan was increased. (depend on spec.)		Pass

Item Test	Voltage Sensor	
Test Procedure		Result
To check if value of the voltage from the specific function showing the status is ok.	Check voltage under Hyperterminal status.	Pass
	Check voltage under GUI	Pass
Item Test	Expander	
Test Procedure		Result
Check channel of expander that function is ok.	Hot-swap expander board under power on status, and expander board could on-line automatically.	Pass
	Check PHY state and negotiated link speed, confirm the PHY contents conform with actual HDD configuration	Pass
	Up connector is substrate type.	Pass
	Down connectors were table type.	Pass
Item Test	Burn-in Test	
Test Procedure		Result
Using performance assessment tool, let JBOD status was maintain full loading on 24 hours. No any error message was showed.	Adjust conf. to 100% read	Pass
	Adjust conf. to 100% write	Pass
AIC	AIC Inc.	REV A3 Page 11 of 15

Item Test	SAS Zoning	
Test Procedure		Result
Applying SAS Zoning function to segment HDD group, and obtain benefit of dual host that could connect the same JBOD simultaneously.	Group8 and Group9 were run independently.	Pass
	Group1 can detect Group8 and Group9.	Pass
	Take HDD for Group8, and all HDD of Group8 could build RAID and run lometer.	Pass
	Take HDD for Group9, and all HDD of Group9 could build RAID and run lometer.	Pass
Item Test	Temperature Sensor	
Test Procedure		Result
When temperature sensor \geq designated degree, the GUI will spring up warning message, and fan speed from the RS232 console showing the status is normal.	T1, T2, warning, Alarm value configuration setting	Pass
	Temperature detected status under GUI	Pass
	Temperature detected status under Hyperterminal	Pass
	Break through alarm value, then the fail led will light up	Pass
	Break through alarm value, beep from buzzer	Pass
	Break through alarm value, RPM of fan is the highest	Pass
AIC	AIC Inc.	REV A3 Page 12 of 15

Item Test	SES Lighting Signal	
Test Procedure		Result
To verify SES lighting signal, using sg3_utils tool to check lighting mode of each status is correct.	Request consistency check in progress	Pass
	Request in critical array	Pass
	Request in failed array	Pass
	Request rebuild/ remap	Pass
	Request rebuild/ remap aborted	Pass
	Request device missing indication	Pass
	Request insert	Pass
	Request removal	Pass
	Request identify	Pass
	Request fault indication	Pass
AIC	AIC Inc.	REV A3 Page 13 of 15

7 RAID Card Test

Test Engineer	Jack Huang		
Model Name	XJ3000-4243 Swap		
Firmware	1.11.5.7		
MFG	1.5.0.5		
Expander Board	B46-LKSAXXE-00A210 1. SN: 506-12091000110001 2. SN: 506-12102600110299		
Backplane	B40-4ATKXXXX00A110 SN: 505-12102600310145		
RAID Card	Adaptec 6405	Driver	7.1.0.00034
HDD Type	3G SAS HDD: Fujitsu / MBA3073RC / 73.5GB 6G SAS HDD: Seagate / ST3600057SS / 600GB Seagate / ST3600002SS / 600GB Seagate / ST31000424SS / 1TB Seagate / ST1000NM0001 / 1TB		
Power Housing	Zippy R2G-5600V4V AC INPUT: 100-240V 47-63Hz 9-4A DC OUTPUT: 600W(MAX)		
Power Module	Zippy GIN-3600V AC INPUT: 100-240V 47-63Hz 9-4A		

RAID Function	Test Procedure	Result
Adaptec 6405 RAID Function	Create/Remove a RAID 0 volume	Pass
	Create/Rebuild/Remove a RAID 1 volume	Pass
	Create/Rebuild/Remove a RAID 5 volume	Pass
	Create/Rebuild/Remove a RAID 6 volume	Pass
	Create/Rebuild/Remove a RAID 10 volume	Pass
	Create/Rebuild/Remove a RAID 50 volume	Pass
	Remove a crashed RAID 0 volume	Pass
	Remove a crashed RAID 1 volume	Pass
	Remove a crashed RAID 5 volume	Pass
	Remove a crashed RAID 6 volume	Pass
	Remove a crashed RAID 10 volume	Pass
	Remove a crashed RAID 50 volume	Pass

8 Summary

Item	Descriptions	Result
Enclosure Function Test	Power Module	Pass
	System FAN	Pass
	Voltage Sensor	Pass
	Expander	Pass
	Burn-in Test	Pass
	SAS Zoning	Pass
	Temperature Sensor	Pass
	SES Lighting Signal	Pass
RAID Function Test	Adaptec 6405 SAS RAID CARD	Pass

** Notes: Test items and test contents depend on spec.